

**CONSTRUCTION PRODUCTS REGULATION (EU) 305/2011
DECLARATION OF PERFORMANCE**

DoP N°: DML001 v3

The logo for ERA, consisting of the letters 'ERA' in a bold, red, sans-serif font, enclosed within a thin black rectangular border.

1. Unique identification code of the product type:

High Security Fortress Single Point Mortice Lock

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

261-31

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

When used with an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and thereafter to ensure that the door remains shut.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

ERA Home Security Ltd
Valiant Way
Wolverhampton
WV9 5GB

Tel: +44 (0)1902 490000

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12209:2003/ AC 2005
Notified testing laboratory No 2812, performed the type testing and issued test reports
Element Materials Technology Rotterdam B.V
Zekeringstraat 33
1014 BV
Amsterdam
Netherlands

8. European Technical Assessment:

N/A

9. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|---|--|------------------------------------|
| Self-closing ability -5.4.2 Closing force -5.1.2 Return force of latch bolt | Grade 8= 200kg door mass with 15N maximum closing force >2.5N | EN 12209:2003/AC 2005 |
| Durability of self-closing action -5.3.1 Durability of latch action | Grade H 200,000 cycles with 10N side Load | |
| Ability to maintain door in closed position and not contribute to the spread of fire -5.5 Suitability for use on fire/smoke doors | Grade 1: suitable for use on fire/smoke resisting doorset assemblies | |
| Control of dangerous substances -5.1.1 Dangerous substances | The materials in this lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ben Penson: Manufacturing & Technical Director



18/12/2020

.....